

Spray-On™

✓ Easy To Use

✓ Fast Acting

✓ Spray On/Rinse Off



1. Spray or brush on surface.
1. Rocíe o aplique con brocha sobre la superficie.



2. Let stand 1-5 minutes, don't allow to dry.
2. Espere de 1 a 5 minutos, no permita que se seque.



3. Rinse with water til foam disappears.
3. Enjuague con agua hasta que desaparezca la espuma.

Spray-On™ FIBERGLASS CLEANER quickly removes marine deposits, oxidation, scum, lime and water line stains from Fiberglass boat hull & bottoms.

El LIMPIADOR DE FIBRA DE VIDRIO **Spray-On™** elimina rápidamente depósitos marinos, óxido, suciedad, cal y manchas de la línea de agua en cascos y fondos de barcos de fibra de vidrio.

DIRECTIONS: READ ENTIRE LABEL BEFORE USING THIS PRODUCT.

Determine if dilution is required and test on inconspicuous area. **DILUTION:** For Heavy Build-Up: (boats left in the water) Use full Strength. For Light Build-up: MIX 1 part Spray-On with 1 part water in plastic pail or container. **DIRECTIONS FOR USE:** Pour into 1-2 Gallon Plastic Home & Garden Pump Sprayer or into plastic pail or container and apply with natural bristle brush. **Surface must be completely dry.** Apply evenly beginning at bottom and working up. Use fine adjustment on sprayer to avoid streaking. Works best in temperatures of 50-85° F. Heavy build-up may require more than one application and the use of a brush. **TIP:** It's not how much you apply but apply evenly. Manufacturer's liability is limited to purchase price of product.

INSTRUCCIONES: LEA LA ETIQUETA COMPLETA ANTES DE USAR ESTE PRODUCTO.

Determine si necesita diluir el producto y haga una prueba en un área poco visible. **DISOLUCIÓN:** Para acumulaciones fuertes: (botes que permanecen en el agua) use sin diluir. Para acumulaciones ligeras: MEZCLE 1 parte de Spray-On con 1 parte de agua en un balde o recipiente de plástico. **INSTRUCCIONES:** Vierta en un recipiente de plástico de 1-2 galones para rociar en hogares y jardines, o en un balde o recipiente de plástico y aplique con una brocha de cerdas naturales. **La superficie debe estar completamente seca.** Aplique de manera pareja, comenzando por abajo y aplicando hacia arriba. Use el control de aspersión fina en el rociador para no vetear. Funciona mejor a temperaturas de 50 a 85° F. Las acumulaciones más fuertes podrían requerir más de una aplicación con brocha. Sugerencia: En vez de aplicar una mayor cantidad, aplique de manera uniforme. La responsabilidad del fabricante se limita al precio de compra del producto.